

Spec Sheet – N1300

Features

- Stainless steel heat exchanger
- 13:1 turndown ratio
- High-capacity hot water flow rates up to 1500L/hr at commercial temperatures.
- 96% gross efficiency
- BMS integration and remote monitoring capacities
- Easy conversion gas orifice
- Built-in flue damper
- Turbo-fan system
- Switching Venturi
- Room sealed and common header flue options
- Cutting edge electronic controls system delivering temperature hot water

Benefits

- Increased durability and warranty
- Optimises gas usage.
- Guarantees a temperature accurate supply of hot water even for the heaviest of users.
- Best in class efficiency
- Easy integration to Building Management System (BMS) and remote monitoring capability.
- Streamlines flue installation and removes the need for additional flue components.
- Extended flue runs of 45+ metres.
- Provides consistent mixture of gas and air to the burner for low turndown ratios.
- Increased performance and efficiency
- Ease of use and unparalleled levels of control



N1300	
Burner	Pre Mix Zero Governor
Heat Exchanger	Stainless Steel
Weight	27kg
Dimensions	670mm x 470mm x 276mm
Maximum Input	47kW
	4.4kW
Turn Down Ratio	10.5:1
Efficiency	96%
Maximum Set Temperature	85°C
Flow Rate at 25ΔT	25.8 L/Min
Flow Rate at 30ΔT	21.5 L/Min
Flow Rate at 35ΔT	18.5 L/Min
Flow Rate at 40ΔT	16.1 L/Min
Flow Rate at 45ΔT	14.4 L/Min
Flow Rate at 50ΔT	12.9 L/Min
Minumum Flow Rate	1.5 L/Min
Max Number of Sequenced Heaters	Up to 24
Flue Run	Up to 46m
Built in Flue Damper	
Air Inlet Filter	
II 2H3B/P、 II 2H3P、 II 2H3+、 II 2L3B/P、 II 2E3+	
Frost Protection	-15°C Internal, -20°C External
New PCB Design	
Controller as standard - lockable, set up of appliance, temperature set up to 75°C, maintenance for engineers	



Rinnai

sales@rinnaiuk.com | 01928 531870